

SwiftEpoxy HB

for Swimming Pools

CHECK LIST

1. HAVE YOU READ the appropriate 'current' Preparation and Application instructions? These are available from your supplier or Macleod Industries. If your substrate is not mentioned specifically in our literature, it is advisable to seek more information from Macleod Industries prior to commencing.

2. MAKE YOUR JOB EASIER by having the right equipment. Here is a start to your check list of equipment for painting your pool.

- Water-blaster (capable of 3000 p.s.i.)
- Stiff bristled broom
- Plastic watering can fitted with rose (for use with hydrochloric acid)
- Pump
- Wet/dry Vac (if needed)
- Brushes and rollers (10-12mm nap roller sleeves)
- Anything else that you think you need

- _____
- _____
- _____

3. CHECK WEATHER CONDITIONS. Do not attempt to paint when substrate temperature is above 25°C or below 5°C or rain is forecast. Note: SwiftEpoxy HB is best applied in the mornings to allow time to cure before night dew settles on surface.

4. HEALTH AND SAFETY ISSUES. Ensure you understand the risks associated with using this product and how it relates to intended use. A "Material Safety Data Sheet" is available on request.

5. SLIPPERY STEPS. If applying paint on steps, you should consider broadcasting triple-washed, silica sand on wet paint to give a non-slip finish.

IMPORTANT TO REMEMBER when using *SwiftEpoxy HB*:

ONLY MIX ONE PACK AT A TIME

- All of part B must be poured into part A. (Do **not** mix part packs)
- Use a flat paddle blade when stirring part B into part A. Do not use an electric drill.
- After thorough stirring allow product to rest **NO MORE THAN 10 MINUTES**, less if temperature is above 20°C.
- After rest period, give another stir and start applying. You have a maximum of 90 minutes in which to use pack, less in higher temperatures.
- Paint in mornings, before the heat of the day.
- Allow 24 hours between coats.
- Allow 7 days for paint to cure (after final coat) before filling pool with water. Do not shock your pool with chemicals immediately after filling. When chemically treating your pool, broadcast ingredients over a large area rather than dumping in one spot.
- Keep your pool balanced appropriately throughout the year. This will increase the life-span of the paint.

FOR YOUR RECORDS.....KEEP THIS IN A SAFE PLACE

COLOUR _____ WHERE PURCHASED _____

QUANTITY _____ BATCH NO _____ DATE PAINTED _____